Sensor Data Sheet

SENSALERT® PLUS

SENSIDYNE®

Carbon Monoxide – Filtered for H_2S & SO_X
(0 - 500 ppm)
Part No. 823-0219-22
FM Performance Certified [1]

Minimum Indicated Concentration	15 ppm
Repeatability	± 2% of Reading
Accuracy[2]	± 5% of Reading
Span Drift	< 5% change per year (typical)
Response Time (Rise)[3]	T_{50}: < 10 seconds
	T_{90}: < 30 seconds, successive exposures
Recovery Time (Fall)[3]	T_{10}: < 30 seconds
Temperature Range	-20° to 50°C (-4° to 122°F)
Humidity Range (continuous)	15–90 %RH, non-condensing
Humidity Range (intermittent)	0–99 %RH, non-condensing
Pressure Range	Ambient atmospheric, ± 1 psi
Expected Sensor Life	3 years from Shipping Date
Recommended Calibration Flow Rate	500 to 1000 cc/min
Oxygen Requirement	1% by volume, minimum
SensAlert 4-Channel Controller	Compatible

[1] For use in an FM Approved SensAlert Plus Transmitter.

[2] When unit is calibrated and serviced at recommended intervals.

[3] Room Temperature.

Cross-Interferences*

Gas	Gas Exposure	Sensor Output
Chlorine	1 ppm	None
Ethylene	1.3 ppm	+1 ppm
Hydrogen	1.7 ppm	+1 ppm
Hydrogen Chloride	5 ppm	None
Hydrogen Cyanide	5 ppm	+1 ppm
Hydrogen Sulfide	50 ppm	+1 ppm
Nitric Oxide	5 ppm	+1 ppm
Nitrogen Dioxide	5 ppm	-1 ppm
Sulfur Dioxide	5 ppm	None

* Interference factors may differ from sensor to sensor, it is not advisable to calibrate with interferent gases.

Sensidyne, LP • 1000 112th Circle N, Suite 100 • St. Petersburg, FL 33716 USA • 800-451-9444 • +1 727-530-3602
+1 727-539-0550 fax • web: www.sensidyne.com • e-mail: info@sensidyne.com

Special Calibration Considerations:
Carbon Monoxide Sensor (PN° 823-0219-22)

Zeroing The Sensor

There are no special zeroing considerations for this sensor. Complete zeroing instructions are provided in Section 3.1 of the SensAlert*Plus* User Manual or SensAlert ASI User Manual.

Span Calibration

It is recommended that this sensor be calibrated at the half-scale concentration of 250 ppm. There are no special calibration considerations for this sensor. Complete span calibration instructions are provided in Section 3.2 of the SensAlert*Plus* User Manual or SensAlert ASI User Manual.

Test-on-Demand Cell

There is no Test-On-Demand cell available for this sensor.